

ARMANO

problem
analysis
solution

kommu...
inspiration
zusammen...
resultat...
definitiv...
prof...
planun...

entwicklung
zielstrebigke...
schafft
leistung
maßnahmen

Differential Pressure Measurement in Submarines



Application:

Pressure monitoring – duplex pressure gauge with differential pressure indicator

for submarine yards, operators of differential pressure measuring instruments



In the standard version, differential pressure gauges are equipped with an additional dial at the lower pointer, with which the differential pressure between both connections can be read.

The problem:

For differential pressures, in some cases it shall be obvious at the first glance whether the pressure is within a certain range. Furthermore, the pressure gauge must remain readable even in the dark (without lighting).



without differential pressure



15 bar differential pressure

Our solution:

Duplex pressure gauges with two special indicator dials, black case and luminescent scale. A red field appears at a certain pressure range, as requested by the customer. Additionally, the white scale is coated with a luminescent colour, which ensures visibility in the dark.



luminescent scale



Well monitored with: DiRCh 100 – 1 Rh

- ◆ Mounting device according to your requirements
- ◆ Case colour fitting to the surroundings
- ◆ Indicator dial design fitted to the requirements on site
- ◆ Also available in stainless steel

www.armano-messtechnik.com

ARMANO Messtechnik GmbH

Location Beierfeld • Am Gewerbehark 9 • 08344 Grünhain-Beierfeld
Tel.: +49 3774 58 – 0 • Fax: +49 3774 58 – 545 • mail@armano-beierfeld.com

Location Wesel • Manometerstraße 5 • 46487 Wesel-Ginderich

Tel.: +49 2803 9130 – 0 • Fax: +49 2803 1035 • mail@armano-wesel.com

AppBe_SB_027

11/2019